



NOTE

THIS DESIGNATION IS SUGGESTED FOR HIGHWAYS ON SERVICE CLASS 3 IF THEY WARRANT PAVING DUE TO SPECIAL CIRCUMSTANCES BUT HAVE AADT LESS THAN 200. THE SERVICE CLASSES ARE IDENTIFIED IN THE ALBERTA FUNCTIONAL CLASSIFICATION SYSTEM MAP.

EARTH CUT SECTION

- * WIDTH OF DITCH - 3.5m STANDARD, 1.5m MINIMUM.
- * BACKSLOPE VARIABLE UP TO MAXIMUM NOTED. 1.5m TO BE LEFT BETWEEN TOP OF BACKSLOPE AND RIGHT-OF-WAY LIMIT AS SHOWN.
- * DITCH WIDTH AND ROUNDING AT TOP OF BACKSLOPE TO BE INCREASED AT BEGINNING AND END OF CUT SECTIONS FOR AESTHETICS.

SUBGRADE AND SURFACING DIMENSIONS

⊙ FOR CALCULATION OF Z AND S VALUES, REFER TO FIGURE CB6-3.50M5 (NEW CONSTRUCTION) AND FIGURE CB6-3.50M7 (WIDENING).

FILL SECTION

- * 4:1 SLOPES FOR AVERAGE FILLS LESS THAN 4.0m.
- * 4:1 SLOPES CAN BE USED ON SHORT SECTIONS OF HIGHWAY FILL UP TO 14m IN HEIGHT (TO ELIMINATE THE NEED FOR GUARDRAIL), PROVIDING THERE ARE NO OBSTRUCTIONS WITHIN OR NEAR THE RIGHT-OF-WAY LIMITS.
- * 3:1 SLOPES OR 2:1 SLOPES MAY BE USED UPON APPROVAL IN AREAS WHERE GUARDRAIL IS TO BE INSTALLED.
- * THE CHOICE BETWEEN 4:1 SLOPE AND GUARDRAIL INSTALLATION ON HIGH EMBANKMENTS IS GENERALLY MADE BASED ON LIFE-CYCLE COST-EFFECTIVENESS.
- * 3:1 SLOPES ARE TO BE USED ON ALL FILLS ADJACENT TO DRAINAGE STRUCTURES OVER 1200mm IN DIAMETER, CATTLE PASSES, OPEN WATER, ETC. WHERE GUARDRAIL INSTALLATION IS NECESSARY FOR HIGHWAY SAFETY.
- * TRANSITION BETWEEN SLOPES SHALL BE ATTAINED BY USING UNIFORMLY VARYING SLOPES. GENERALLY THE MINIMUM LENGTH OF TRANSITION SHALL NOT BE LESS THAN 30m.
- * BERM ALSO TO BE CONSTRUCTED ADJACENT TO OPEN WATER.

Ⓐ	PAVEMENT SIDESLOPE AND DWG TITLE	PM	16/06/06
Ⓓ	SUBGRADE AND SURFACING NOTES	BK	03/31/06
Ⓒ	ADDED SURFACING DIMENSIONS NOTE	TDN	06/98
Ⓔ	CHANGE IN DESIGN SPEED/FILL NOTES	BK	06/93
No.	REVISIONS	BY	DATE

Approved:
 ORIGINAL SIGNED BY ALLAN KWAN
 Executive Director,
 Technical Standards Branch
 Alberta Infrastructure and Transportation
 Date: DECEMBER 6, 1980

STANDARD CROSS-SECTION FOR RCU-208-110/100

Prepared By: R.T.	Checked By: BK	Scale: N.T.S.	Dwg No.: CB6-2.3M41
-------------------	----------------	---------------	---------------------

