



A METAL ANCHOR 40mm STEEL PIPE OR EQUIVALENT. MIN. LENGTH 2.0m MIN. WEIGHT 5.4 kg/LIN. m
 (2 REQUIRED FOR EACH COUPLING BAND ON DOWNDRAIN PIPE)

C TWO PIECE COUPLING BAND WITH ANCHOR PLATES

NOTE:

1. ALL JOINTS TO BE ANCHORED.
2. MAXIMUM SPACING OF ANCHORS NOT TO EXCEED 6m
3. ALL 40mm ANCHOR PIPE TO BE DRILLED 15cm FROM TOP END TO RECEIVE 12mm DIAMETER BOLT.
4. 15cm-12mm DIAMETER BOLT TO BE SUPPLIED WITH EACH ANCHOR.
5. TEMPORARY ASPHALT STABILIZED BASE COURSE CURB WHEN REQUIRED TO BE CONSTRUCTED ALONG OUTSIDE OF SHOULDER TO DIRECT SURFACE DRAINAGE.

Alberta TRANSPORTATION Engineering Division	DWG. NO.	CB-6 2.4.M11
	Date	May, 1979
	Original	
	Revision	

DETAILS
 of
CORRUGATED STEEL DOWNDRAIN PIPE
 with
STORM DRAIN INLET

OBSOLETE
 March, 2022