



GENERAL NOTES

- DIMENSIONS ARE GIVEN IN mm. DETAILS ARE NOT TO SCALE.
 - ASPHALT IMPREGNATED FIBRE BOARD (AIFB) SHALL CONFORM TO THE CURRENT ASTM SPECIFICATION D1751 FOR PREFORMED EXPANSION JOINT FILLERS.
 - ② WELDED WIRE MESH (WWM) SHALL BE 152 x 152 MW25.8 x 25.8, SUPPLIED IN ROLLS, LAPPED A MINIMUM OF 152 mm.
 - ALL CONCRETE SHALL BE PLACED IN ALTERNATE HORIZONTAL (OR VERTICAL) COURSES. FIRST COURSE SHALL HAVE SET UP PRIOR TO PLACING ADJOINING COURSE.
 - ALL JOINTS SHALL BE FORMED USING A SIDEWALK TYPE GROOVING TOOL.
 - SLAB SHALL BE GIVEN A CLASS 6 SIDEWALK FINISH.
- DRAFTING STANDARDS PAGE: 2.5

SUPERSEDED
 BY S-1409-99-REV1
 (19-04-20)
 ④

				Alberta TRANSPORTATION AND UTILITIES BRIDGE ENGINEERING BRANCH			
				STANDARD CONCRETE SLOPE PROTECTION			
④							
③							
②	94-11-30	GENERAL NOTES AND REBAR NOTE	RJR				
①	87-03-23	REDRAWN FROM S-1409	DHQ				
NO	DATE	REVISIONS	BY				
DESIGNED	DRAWN	DATE	APPROVED	SIGNATURE	DATE	PAGE	DRAWING
DHQ	MIK	87-03-23	EXECUTIVE DIRECTOR	<i>[Signature]</i>	17/3/87	8.5	S-1409-87