



GENERAL NOTES

- DIMENSIONS ARE GIVEN IN mm. DETAILS ARE NOT TO SCALE.
- WELDED WIRE MESH (WWM) SHALL BE 152 x 152 MW25.8 x 25.8, SUPPLIED IN FLAT SHEETS, LAPPED A MINIMUM OF 152 mm AND SHALL BE SUPPLIED BY THE CONTRACTOR.
- ALL CONCRETE SHALL BE PLACED IN ALTERNATE HORIZONTAL (OR VERTICAL) COURSES. FIRST COURSES SHALL HAVE SET UP PRIOR TO PLACING ADJOINING COURSES.
- ALL JOINTS SHALL BE FORMED USING A SIDEWALK TYPE GROOVING TOOL.
- SLAB SHALL BE GIVEN A CLASS 5 FINISH.

**SUPERSEDED BY S-1409-99
REVISION 4, 2007-09-12**

				Alberta TRANSPORTATION AND UTILITIES TECHNICAL STANDARDS BRANCH	
NO	DATE	REVISIONS	BY		
④					
③	2006-06-01	GENERAL NOTES - CONCRETE FINISH	JWG		
②	2005-06-01	TOE CUT-OFF WALL DETAIL REVISED	RY		
①	99-04-20	REDRAWN FROM S-1409-87	RY		
DESIGNED	DRAWN	DATE	APPROVED	SIGNATURE	DATE
DHQ	WS	99-04-20	EXECUTIVE DIRECTOR	<i>[Signature]</i>	11/24/87
				PAGE	DRAWING
				8.5	S-1409-99