



GENERAL NOTES

- DIMENSIONS ARE GIVEN IN mm. DETAILS ARE NOT TO SCALE.
- WELDED WIRE MESH (WWM) SHALL BE 152 x 152 MW25.8 x 25.8, SUPPLIED IN FLAT SHEETS, LAPPED A MINIMUM OF 152 mm AND SHALL BE SUPPLIED BY THE CONTRACTOR.
- ALL CONCRETE SHALL BE PLACED IN ALTERNATE HORIZONTAL (OR VERTICAL) COURSES. FIRST COURSES SHALL HAVE SET UP PRIOR TO PLACING ADJOINING COURSES.
- ALL JOINTS SHALL BE FORMED USING A SIDEWALK TYPE GROOVING TOOL.
- SLAB SHALL BE GIVEN A CLASS 5 FINISH.

2009-05-21	CUT-OFF WALL REVISED	CM CM
2007-09-12	DETAIL P ADDED - GALV FLASHING	RY
2006-06-01	GENERAL NOTES - CONCRETE FINISH	GW
2005-06-01	TOE CUT-OFF WALL DETAIL REVISED	RY
99-04-20	REDRAWN FROM S-1409-87	RY
NO	DATE	REVISIONS
DESIGNED	DRAWN	DATE
DH0	WS	99-04-20
APPROVED	SIGNATURE	DATE
EXECUTIVE DIRECTOR	<i>[Signature]</i>	May 8/87
PAGE	DRAWING	
8.5	S-1409-99	

Alberta TRANSPORTATION AND UTILITIES TECHNICAL STANDARDS BRANCH

CONCRETE SLOPE PROTECTION

DESIGNED	DRAWN	DATE	APPROVED	SIGNATURE	DATE	PAGE	DRAWING
DH0	WS	99-04-20	EXECUTIVE DIRECTOR	<i>[Signature]</i>	May 8/87	8.5	S-1409-99