



GENERAL NOTES

- DIMENSIONS ARE GIVEN IN mm. DETAILS ARE NOT TO SCALE.
- PLACING OF THE SANDBAGS SHALL START AT THE BOTTOM CENTRE OF THE DISHED AREA AND SHALL PROCEED IN A CONTINUOUS SPIRAL FASHION OUTWARD UNTIL THE ENTIRE DISHED AREA IS COVERED. EACH SANDBAG SHALL LAP OVER THE EDGES OF THE PREVIOUSLY PLACED BAGS.
- SANDBAGS AND CLASS A CONCRETE SHALL BE SUPPLIED BY THE CONTRACTOR.

DRAFTING STANDARDS PAGE 3.6

SUPERSEDED
 BY 5-1410-91-REV 1
 ON SHEET 4
 (91-01-29)

				Alberta TRANSPORTATION AND UTILITIES BRIDGE ENGINEERING BRANCH			
				STANDARD DRAIN TROUGH TERMINAL PROTECTION			
DESIGNED	DRAWN	DATE	APPROVED	SIGNATURE	DATE	PAGE	DRAWING
DHO	MIK	87-03-02	EXECUTIVE DIRECTOR	<i>[Signature]</i>	12/8/87	9.3	S-1410-87
NO	DATE	REVISIONS		BY			
△	87-03-02	REDRAWN FROM S-1410		DHO			

3