



3 000 ϕ SINGLE LAYER OF OVERLAPPING CONCRETE FILLED BAGS

PLAN

LEVEL

130 THICK BAGGED CONCRETE RIPRAP

SECTION

GENERAL NOTES

- DIMENSIONS ARE GIVEN IN mm. DETAILS ARE NOT TO SCALE.
- PLACING OF BAGGED CONCRETE RIPRAP SHALL START AT THE BOTTOM CENTRE OF THE WASHED AREA AND SHALL PROCEED IN A CONTINUOUS SPIRAL FASHION OUTWARD UNTIL THE ENTIRE DISH IS COVERED. EACH CONCRETE FILLED BAG SHALL LAP OVER THE EDGES OF THE PREVIOUSLY PLACED BAGS.

SUPERSEDED
 BY S-1410-91 (99.03.29)
 REV B
 5
 5
 DRAFTING STANDARDS PAGE: 2.6

④			
③			
②	94-11-30	GENERAL NOTES	RJR
①	91-01-29	REDRAWN FROM S-1410-87	DHQ
NO	DATE	REVISIONS	BY

Alberta TRANSPORTATION AND UTILITIES
 BRIDGE ENGINEERING BRANCH

**STANDARD
 DRAIN TROUGH
 TERMINAL PROTECTION**

DESIGNED DHQ	DRAWN MIK	DATE 91-01-29	APPROVED EXECUTIVE DIRECTOR	SIGNATURE <i>mm Boyd</i>	DATE Jan 30/91	PAGE 9.3	DRAWING S-1410-91
-----------------	--------------	------------------	--------------------------------	-----------------------------	-------------------	-------------	----------------------