



**GENERAL NOTES**

- DIMENSIONS ARE GIVEN IN mm. DETAILS ARE NOT TO SCALE.
- PLACING OF BAGGED CONCRETE RIPRAP SHALL START AT THE BOTTOM CENTRE OF THE DISHED AREA AND SHALL PROCEED IN A CONTINUOUS SPIRAL FASHION OUTWARD UNTIL THE ENTIRE DISH IS COVERED. EACH CONCRETE FILLED BAG SHALL LAP OVER THE EDGES OF THE PREVIOUSLY PLACED BAGS.

2

6

DRAFTING STANDARDS PAGE: 2.6

<b>TRANSPORTATION AND UTILITIES TECHNICAL STANDARDS BRANCH</b>			
<b>STANDARD DRAIN TROUGH TERMINAL PROTECTION</b>			
DESIGNED	DRAWN	DATE	APPROVED
DHQ	MIK	91-01-29	EXECUTIVE DIRECTOR
NO	DATE	REVISIONS	BY
4			
3	99-03-29	BEB CHANGED TO TSB	RY
2	94-11-30	GENERAL NOTES	RJR
1	91-01-29	REDRAWN FROM S-1410-87	DHQ
SIGNATURE		DATE	PAGE
			9.3
DRAWING		S-1410-91	