



**GENERAL NOTES**

- DIMENSIONS ARE GIVEN IN mm. DETAILS ARE NOT TO SCALE.
- PLACING OF BAGGED CONCRETE RIPRAP SHALL START AT THE BOTTOM CENTRE OF THE DISHED AREA AND SHALL PROCEED IN A CIRCULAR LAYERED FASHION UPWARD UNTIL THE ENTIRE DISH IS COVERED. EACH CONCRETE FILLED BAG SHALL LAP OVER THE EDGES OF THE PREVIOUSLY PLACED BAGS.

4	2003-03-21	GENERAL NOTES	JT
3	99-03-29	BEB CHANGED TO TSB	RY
2	94-11-30	GENERAL NOTES	RJR
1	91-01-29	REDRAWN FROM S-1410-87	DHQ
NO	DATE	REVISIONS	BY
DESIGNED	DRAWN	DATE	APPROVED
DHQ	MIK	91-01-29	EXECUTIVE DIRECTOR

**Alberta** TRANSPORTATION AND UTILITIES  
TECHNICAL STANDARDS BRANCH

**STANDARD  
DRAIN TROUGH  
TERMINAL PROTECTION**

SIGNATURE: *[Signature]* DATE: \_\_\_\_\_ PAGE: 9.3 DRAWING: S-1410-91