



WALL OR PIER  
SHAFT DETAIL

SLAB DETAIL

GENERAL NOTES

- DIMENSIONS ARE GIVEN IN mm. DETAILS ARE NOT TO SCALE.
- SURFACES OF HORIZONTAL JOINTS SHALL BE THOROUGHLY CONSOLIDATED AND INTENTIONALLY LEFT IN A ROUGHENED CONDITION.
- JOINTS SHALL BE CLEANED OF SURFACE LAITANCE AND OTHER FOREIGN MATERIALS PRIOR TO PLACING NEW CONCRETE.
- ▲ • REFER TO ALBERTA TRANSPORTATION'S PRODUCT LIST UNDER "CRACK TREATMENT/CONCRETE CRACK FILLER" FOR APPROVED GRAVITY FLOW EPOXY PRODUCTS.

				<b>Alberta</b> TRANSPORTATION AND UTILITIES TECHNICAL STANDARDS BRANCH	
▲					
▲	2010-01-21	SLAB DETAIL & GENERAL NOTES REVISED	DB		
▲	01-06-06	SLAB DETAIL JOINT REVISED	RY		
▲	99-04-12	REDRAWN FROM S-1412-98 REV ▲	RY		
NO	DATE	REVISIONS	BY		
DESIGNED	DRAWN	DATE	APPROVED	SIGNATURE	DATE
RY	WS	99-04-12	EXECUTIVE DIRECTOR	<i>[Signature]</i>	17 May 07
				PAGE	DRAWING
				4.35	S-1412-99