



PLAN  
NTS

**SIGNING MATERIALS LIST**

SIGN NO.	MESSAGE OR DESCRIPTION	TOTAL NO. REQ'D FROM DRAWING	NUMBER ON HAND	ADDITIONAL SIGNS REQUIRED
RA-1 OR RA-2	STOP OR YIELD	6		
WB-1	STOP AHEAD	4		
WD-101B	BRIDGE CONSTRUCTION AHEAD	2		
WD-102	BEGIN DETOUR 300 m	2		
WD-103	DETOUR NEXT ____ km	2		
WD-104	BARRICADE AHEAD	2		
WD-116	BARRICADE STANDS	28		
WD-116-1L	BARRICADE LEFT	11		
WD-116-1R	BARRICADE RIGHT	11		
WD-116-3	BARRICADE-BRIDGE OUT	6		
WD-116-5	BARRICADE ARROW	8		
WD-154	END OF CONSTRUCTION	2		
	DETOUR RIGHT	4		
	DETOUR LEFT	4		

**GENERAL NOTES**

- THIS DRAWING ILLUSTRATES TRAFFIC SIGNING AND DELINEATION REQUIREMENTS FOR BRIDGE CONSTRUCTION
- ORANGE FLAGS TO BE INSTALLED ON ALL SIGNS DURING DAYLIGHT HOURS
- FLASHERS TO BE INSTALLED AT ALL BRIDGE CONSTRUCTION AHEAD SIGNS AND A FEW ON BARRICADES AT NIGHT AS DETERMINED BY ENGINEER
- ALL SIGNS NOT IN EFFECT TO BE COVERED OR TAKEN DOWN
- ALL SIGNS SHOWN ARE AT MINIMUM DISTANCES WHICH MAY BE INCREASED OR REGULATED DEPENDENT ON CONDITIONS
- ALL SIGNS ARE TO BE KEPT CLEAN, DAMAGED OR WORN OUT SIGNS ARE TO BE REPLACED
- BRIDGE ENGINEER OR PROJECT MANAGER MAY MAKE ADJUSTMENTS TO SIGNS AS REQUIRED TO SUIT LOCAL OR SITE CONDITIONS
- STOP SIGNS OR YIELD SIGNS SHOULD BE EXAMINED IN THE FIELD. THESE SIGNS SHOULD ONLY BE ADDED IF THERE IS SIGNIFICANT CHANGE IN TRAFFIC VOLUMES. IF THERE ARE EXISTING SIGNS, DO NOT CHANGE EXISTING RIGHT-OF-WAY RULES

**SUPERSEDED**  
BY REVISION  $\Delta$  (76-11-28)  
BY TEB 1.110  
SHEET 0

DESIGNED CRW		DRAWN HWM		DATE 95-03-17		CHECKED [Signature]		DATE March 23/95		STREAM		LOCATION		HIGHWAY		FILE		SHEET 1 of 1		DRAWING S-1441-95	
APPROVED [Signature] EXECUTIVE DIRECTOR BRIDGE ENGINEERING DATE: March 23/95										<b>Alberta TRANSPORTATION AND UTILITIES</b> BRIDGE ENGINEERING BRANCH <b>TYPICAL DETOUR SIGNING FOR BRIDGE CONSTRUCTION ON LOCAL ROADS</b>											

NOTE: THIS DRAWING HAS BEEN REDUCED TO 22"X34" DO NOT SCALE