



**GENERAL NOTES**

1. Red flags to be installed on all signs for daylight hours.
2. Flares to be placed at all signs at night.
3. All signs not in effect to be covered or taken down.
4. Special signs may be required on some projects.
5. All signs shown are at a min. distance and may be increased or regulated by conditions.
6. Flagman: Flagman must stand within the 25 M.P.H. zone. Flagman must wear reflectorized jacket and arm bands at all times. Stop and Go paddles shall be used both night and day. Signal wands are to be used on flashlights at night.
7. Painting: "CAUTION PAINT SPRAY GUNS IN OPERATION" signs to be erected at a min. distance of 1200' from end of bridge during painting operations. Stop signs to be at a min. distance of 400' from end of bridge when winds are calm. This distance shall be increased as required by direction and velocity of wind causing paint spray to drift.
8. All signs to be kept clean. Damaged or worn out signs to be replaced.

APPROVED: *[Signature]*  
 CHIEF BRIDGE ENGINEER

NOTE: This drawing to supersede S 763A and S 763 B

TRAFFIC SIGNS  
 FOR BRIDGE  
 CONSTRUCTION & MAINTENANCE



**GOVERNMENT OF THE PROVINCE OF ALBERTA**  
 DEPARTMENT OF HIGHWAYS  
 BRIDGE BRANCH, EDMONTON

NO.	DATE	DESCRIPTION	CHECKED	BY
4				
3				
2				
1	Dec. 18/63	Signing Layout revised	H.G.A	F.M.

REVISIONS

FILE NO. 3190 HWY. NO. \_\_\_\_\_  
 LOCATION \_\_\_\_\_ SCALE N.T.S.  
 STREAM \_\_\_\_\_ SHEET 1 OF 1

DWG. NO.  
**S 763 C**

AT & U - RECORDS CENTRE  
 F198872