



- GENERAL NOTES-**
- Fabrication is to be in accordance with the A A S H O Specifications for Highway Bridges, 1961 edition.
 - The Fabricator shall submit shop drawings and they shall be approved by the Department before fabrication is started. The checking of shop drawings is to be considered as assisting the Fabricator and shall not relieve him of responsibility for error or omissions.
 - All shop splices are to be shown on the shop drawings.
 - All steel surfaces not in contact with steel or concrete to receive one Shop coat of red lead, iron oxide, oil alkyd type paint conforming to the Canadian Government Specification Board - Specification 1-GP-140A.
 - Steel shall conform to the current A.S.T.M. Specification A36

SUPERSEDED

SUPERSEDED

NOTE: Anchor bolt assemblies to be hot dip galvanized after fabrication.

3'-9 SIDEWALK VERTICAL BAR TYPE HANDRAIL DETAIL

GOVERNMENT OF THE PROVINCE OF ALBERTA
DEPARTMENT OF HIGHWAYS
BRIDGE BRANCH, EDMONTON

NO.	DATE	DESCRIPTION	BY
1	Feb. 15/65	Anchor bolt dimension changed	V.G.B.
2	Sept. 15/66	Redrawn from 6-752	B.W.S.

FILE NO. _____ HWY. NO. _____ DWG. NO. **5-865**

LOCATION _____ SCALE _____ SHEET _____ OF _____

DESIGNED BY: L. Kohlmann
 CHECKED BY: _____
 DATE: _____
 APPROVED BY: _____
 DATE: _____