

ALBERTA TRANSPORTATION AND
ECONOMIC CORRIDORS GRMP
NORTH CENTRAL (ATHABASCA AND FORT
McMURRAY DISTRICTS)
INSTRUMENTATION MONITORING- SPRING 2025



Site Number	Location	Name	Hwy	km
NC025	HWY 646:04 C1 16.082	Lindbergh Hill	646:04	Km 16.1
Legal Description: 15-27-56-5 W4		UTM Co-ordinates		
		12U E 522385	N	5969334

Current Monitoring:	22-May-2025	Previous Monitoring	5-June-2024
Instruments Read By:	Mr. Niraj Regmi, G.I.T and Mr. Godfred Etiendem, of Thurber		

Instruments Read During This Site Visit			
Slope Inclinometers (SIs): SI02-1 and SI07-1 to 07-3	Pneumatic Piezometers (PN): N/A	Vibration Wire Piezometers (VW): N/A	Standpipe Piezometers (SP): SP02-1 and SP02-4
Load Cell (LC): VC1463 through VC1468	Strain Gauges: N/A	SAAs: N/A	Others:

Readout Equipment Used			
Slope Inclinometers: RST Digital Inclinator probe with 2 ft wheelbases and RST pocket readout	Pneumatic Piezometers:	Vibration Wire Piezometers:	Standpipe Piezometers: Heron dipmeter
Load Cell: RST Digital readout unit	Strain Gauges:	SAAs:	Others:
Notes:			

Discussion	
Zones of New Movement:	None
Interpretation of Monitoring Results:	SI02-1, installed in the south ditch of the highway, continued to show no discernible movement. The movements in the SIs installed in the piles were as follows: - SI07-1 = - 3.3 mm pile head movement over 0.4 m to 12.0 m depth - SI07-2 = 24.4 mm pile head movement over 0.3 m to 16.7 m depth - SI07-3 = 47.9 mm pile head movement over 0.2 m to 13.6 m depth. SI07-1, located in the western segment of the wall, showed rates of movement of 0.8 mm/yr and 1.4 mm/yr, over 0.4 m to 12.0 m depth and 0.4 m to 20.0 m depth, respectively since the spring 2024 readings. SI07-2, located in the middle segment of the pile wall, showed rates of movement of 1.2 mm/yr and 1.5 mm/yr, over 0.3 m to 11.2 m depth and 0.3 m to 16.7 m depth, respectively since the spring 2024 readings.

	SI07-3, located in the eastern segment of the wall, showed a rate of movement of 4.5 mm/yr over 0.2 m to 5.6 m depth, and a rate of movement of 4.0 mm/yr over 0.2 m to 13.6 m depth, since the spring of 2024 readings. Standpipe piezometer SP02-1 showed a decrease in groundwater level of 0.02 m since the spring of 2024 readings. SP02-4 showed an increase in groundwater level of 1.23 m since the spring of 2024 readings. Load cell VC1463 showed a decrease in measured load of 0.03 kN since the spring of 2024 readings, and a decrease of 46.50 kN since the spring of 2022 readings. The large decrease in the load in VC1463 is likely due to one of the vibrating wires functioning incorrectly. VC1464, VC1465, VC1466 and VC1468 showed increases in measured load of 0.16 kN, 5.41 kN, 0.37 kN, and 0.32 kN, respectively, since the spring of 2024 readings. VC1467 showed a decrease in measured load of 0.3 kN, since the spring of 2024 readings. VC1463, VC1464 and VC1467 currently have three of the four vibrating wire channels functioning so the measured load is the average of the functioning channels. VC1465 currently has only one wire functioning. In general, the instrumentation monitoring results indicate that the pile wall has performed well since construction completion.
Future Work:	The instruments should be read again in the spring of 2026.
Instrumentation Repairs:	No instrument repairs are required at this time.
Additional Comments:	

Attachments:	• Table NC025-1 Spring 2025 – HWY 646:02 Lindbergh Hill, Slope Inclinator Instrumentation Reading Summary • Table NC025-2 Spring 2025 – HWY 646:02 Lindbergh Hill, Standpipe Piezometer Instrumentation Reading Summary • Table NC025-3 Spring 2025 – HWY 646:02 Lindbergh Hill, Load Cell Instrumentation Reading Summary • Statement of Limitations and Conditions • APPENDIX A – NC025-1 SPRING 2025 - o Field Inspector's report - o Site Plan Showing Approximate Instrument Locations (Drawing No. 32122-NC025) - o SI Reading Plots - o Figure NC025-1 (Piezometric Depths) - o Figure NC025-2 (Load Cell Readings)
----------------------------	---

We trust this report meets your requirements at present. If you have any questions, please contact the undersigned at your convenience.

Yours very truly,
Thurber Engineering Ltd.
Tarek Abdelaziz, Ph.D., P. Eng.
Partner | Senior Geotechnical Engineer

Lucas Green, P.Eng.
Geotechnical Engineer

Table NC025-1: Spring 2025– Hwy 646:02 Lindbergh Hill Slope Inclinator Instrumentation Reading Summary

Date Monitored: May 22, 2025

INSTRUMENT #	DATE INITIALIZED	TOTAL CUMULATIVE RESULTANT MOVEMENT AND DEPTH OF MOVEMENT TO DATE (mm)	MAXIMUM RATE OF MOVEMENT (mm/yr)	CURRENT STATUS OF SI	DATE OF PREVIOUS READING	INCREMENTAL MOVEMENT SINCE PREVIOUS READING (mm)	CURRENT RATE OF MOVEMENT (mm/yr)	CHANGE IN RATE OF MOVEMENT SINCE PREVIOUS READING (mm/yr)
SI02-1	Sept. 9, 2002	No discernible movement	N/A	Operational	June 5, 2024	N/A	N/A	N/A
SI02-2	Sept. 9, 2002	N/A	47.6 mm/yr between Sept. 2002 and Oct. 2002	Sheared off	Oct. 12, 2006	N/A	N/A	N/A
SI02-3	Sept. 9, 2002	N/A	52.8 mm/yr between Sept. 2002 and Oct. 2002	Sheared off	Oct. 2006	N/A	N/A	N/A
SI02-4	Sept. 9, 2002	N/A	65.1 mm/yr between Sept. 2002 and Oct. 2002	Sheared off	Oct. 12, 2006	N/A	N/A	N/A
SI06-1	Apr. 4, 2006	N/A	207.9 mm/yr between Apr. 2006 and May 2006	Sheared off	Oct. 12, 2006	N/A	N/A	N/A
SI06-2	Apr. 6, 2006	N/A	430.4 mm/yr between Apr. 2006 and May 2006	Sheared off	Oct. 12, 2006	N/A	N/A	N/A

Drawing 32122-NC025 in Appendix A provides a sketch of the approximate location of the monitoring instrumentation for this site.

Table NC025-1 – Continued: Spring 2025 – Hwy 646:02 Lindbergh Hill Slope Inclinator Instrumentation Reading Summary

Date Monitored: May 22, 2025

INSTRUMENT #	DATE INITIALIZED	TOTAL CUMULATIVE RESULTANT MOVEMENT AND DEPTH OF MOVEMENT TO DATE (mm)	MAXIMUM RATE OF MOVEMENT (mm/yr)	CURRENT STATUS OF SI	DATE OF PREVIOUS READING	INCREMENTAL MOVEMENT SINCE PREVIOUS READING (mm)	CURRENT RATE OF MOVEMENT (mm/yr)	CHANGE IN RATE OF MOVEMENT SINCE PREVIOUS READING (mm/yr)
SI06-3	Aug. 22, 2006	N/A	445.6 mm/yr between Aug. 22 and 30, 2006	Sheared Off	Oct. 12, 2006	N/A	N/A	N/A
SI06-4	Aug. 22, 2006	N/A	194.4 mm/yr between Aug. 22 and Aug. 30, 2006	Sheared Off	Oct. 12, 2006	N/A	N/A	N/A
SI07-1 (Pile #14)	May 22, 2007	-3.3 over 0.4 m to 12.0 m depth in 20° direction	84.8 mm/yr between May 2007 and June 2007	Operational	June 5, 2024	0.8	0.8	1.4
		-1.4 over 0.4 m to 20.0 m depth in 20° direction	92.2 mm/yr between May 2007 and June 2007			1.4	1.4	2.7
SI07-2 (Pile #28)	May 22, 2007	21.6 over 0.3 m to 11.2 m depth in 20° direction	262.7 mm/yr between May 2007 and June 2007	Operational	June 5, 2024	1.2	1.2	1.5
		22.4 over 0.3 m to 16.7 m depth in 20° direction	258.0 mm/yr between May 2007 and June 2007			1.4	1.5	2.2

Drawing 32122-NC025 in Appendix A provides a sketch of the approximate location of the monitoring instrumentation for this site.

Table NC025-1 – Continued: Spring 2025 – Hwy 646:02 Lindbergh Hillslope Inclinator Instrumentation Reading Summary

Date Monitored: May 22, 2025

INSTRUMENT #	DATE INITIALIZED	TOTAL CUMULATIVE RESULTANT MOVEMENT AND DEPTH OF MOVEMENT TO DATE (mm)	MAXIMUM RATE OF MOVEMENT (mm/yr)	CURRENT STATUS OF SI	DATE OF PREVIOUS READING	INCREMENTAL MOVEMENT SINCE PREVIOUS READING (mm)	CURRENT RATE OF MOVEMENT (mm/yr)	CHANGE IN RATE OF MOVEMENT SINCE PREVIOUS READING (mm/yr)
SI07-3 (Pile #38)	May 22, 2007	45.1 over 0.2 m to 5.6 m depth in 10° direction	158.5 mm/yr between Jun. 2007 and July 2007	Operational	June 5, 2024	4.3	4.5	4.4
		47.9 over 0.2 m to 13.6 m depth in 10° direction	149.8 mm/yr between June 2007 and July 2007			3.9	4.0	3.4

Drawing 32122-NC025 in Appendix A provides a sketch of the approximate location of the monitoring instrumentation for this site.

Table NC025-2: Spring 2025 – Hwy 646:02 Lindbergh Hill Standpipe Piezometer Instrumentation Reading Summary

Date Monitored: May 22, 2025

INSTRUMENT #	DATE INITIALIZED	TIP ELEV. (m)	GROUND ELEV. (m)	CURRENT STATUS	HIGHEST MEASURED GROUNDWATER LEVEL BGS (m)	CURRENT GROUNDWATER DEPTH BGS (m)	PREVIOUS GROUNDWATER DEPTH BGS (m)	CHANGE IN WATER LEVEL SINCE PREVIOUS READING (m)
SP02-1	N/A	998.320	1004.50	Operational	999.2 on May 7, 2007 (5.32 mBGS)	998.31 (6.19 mBGS)	998.33 (6.17 mBGS)	-0.02
SP02-3A	N/A	993.99	1002.71	Destroyed	998.11 on Oct. 29, 2003 (4.6 mBGS)	N/A	N/A	N/A
SP02-3	N/A	990.44	1002.71	Destroyed	991.41 on Oct. 3, 2002 (11.3 mBGS)	N/A	N/A	N/A
SP02-4	N/A	989.01	997.45	Operational	996.44 on May 24, 2017 (1.01 mBGS)	995.62 (1.83 mBGS)	994.39 (3.06 mBGS)	1.23
SP06-1	N/A	986.09	1002.20	Destroyed	989.89 on May 30, 2006 (12.3 mBGS)	N/A	N/A	N/A

Drawing 32122-NC025 in Appendix A provides a sketch of the approximate location of the monitoring instrumentation for this site.

Table NC025-3: Spring 2025 – Hwy 646:04 Lindbergh Hill Load Cell Instrumentation Reading Summary

Date Monitored: May 22, 2025

SERIAL #	ANCHOR NUMBER	DESIGN LOAD (kN)	DATE INSTALLED	MEASURED FORCE (kN)	PREVIOUS READING (kN)	CHANGE IN FORCE SINCE PREVIOUS READING (kN)
VC 1463	G37	240	Jul. 6, 2007	163.24*	163.27*	-0.03
VC 1464	G28U	240	Jul. 6, 2007	219.62*	219.46*	0.16
VC 1465	G28L	240	Jul. 6, 2007	154.23**	148.81**	5.42
VC 1466	G19L	330	Jul. 17, 2007	314.81	314.44	0.37
VC 1467	G9U	330	Jul. 6, 2007	275.29*	275.59*	-0.30
VC 1468	G19U	330	Jul. 6, 2007	232.87	232.55	0.32

Drawing 32122-NC025 in Appendix A provides a sketch of the approximate location of the monitoring instrumentation for this site.

* The estimated loads for VC1463, VC1464, and VC1467 are based on the average readings from 3 wires instead of 4.

** The estimated load for VC1465 is only based on one operating vibrating wire.

STATEMENT OF LIMITATIONS AND CONDITIONS

1. STANDARD OF CARE

This Report has been prepared in accordance with generally accepted engineering or environmental consulting practices in the applicable jurisdiction. No other warranty, expressed or implied, is intended or made.

2. COMPLETE REPORT

All documents, records, data and files, whether electronic or otherwise, generated as part of this assignment are a part of the Report, which is of a summary nature and is not intended to stand alone without reference to the instructions given to Thurber by the Client, communications between Thurber and the Client, and any other reports, proposals or documents prepared by Thurber for the Client relative to the specific site described herein, all of which together constitute the Report.

IN ORDER TO PROPERLY UNDERSTAND THE SUGGESTIONS, RECOMMENDATIONS AND OPINIONS EXPRESSED HEREIN, REFERENCE MUST BE MADE TO THE WHOLE OF THE REPORT. THURBER IS NOT RESPONSIBLE FOR USE BY ANY PARTY OF PORTIONS OF THE REPORT WITHOUT REFERENCE TO THE WHOLE REPORT.

3. BASIS OF REPORT

The Report has been prepared for the specific site, development, design objectives and purposes that were described to Thurber by the Client. The applicability and reliability of any of the findings, recommendations, suggestions, or opinions expressed in the Report, subject to the limitations provided herein, are only valid to the extent that the Report expressly addresses proposed development, design objectives and purposes, and then only to the extent that there has been no material alteration to or variation from any of the said descriptions provided to Thurber, unless Thurber is specifically requested by the Client to review and revise the Report in light of such alteration or variation.

4. USE OF THE REPORT

The information and opinions expressed in the Report, or any document forming part of the Report, are for the sole benefit of the Client. NO OTHER PARTY MAY USE OR RELY UPON THE REPORT OR ANY PORTION THEREOF WITHOUT THURBER'S WRITTEN CONSENT AND SUCH USE SHALL BE ON SUCH TERMS AND CONDITIONS AS THURBER MAY EXPRESSLY APPROVE. Ownership in and copyright for the contents of the Report belong to Thurber. Any use which a third party makes of the Report, is the sole responsibility of such third party. Thurber accepts no responsibility whatsoever for damages suffered by any third party resulting from use of the Report without Thurber's express written permission.

5. INTERPRETATION OF THE REPORT

- a) Nature and Exactness of Soil and Contaminant Description: Classification and identification of soils, rocks, geological units, contaminant materials and quantities have been based on investigations performed in accordance with the standards set out in Paragraph 1. Classification and identification of these factors are judgmental in nature. Comprehensive sampling and testing programs implemented with the appropriate equipment by experienced personnel may fail to locate some conditions. All investigations utilizing the standards of Paragraph 1 will involve an inherent risk that some conditions will not be detected and all documents or records summarizing such investigations will be based on assumptions of what exists between the actual points sampled. Actual conditions may vary significantly between the points investigated and the Client and all other persons making use of such documents or records with our express written consent should be aware of this risk and the Report is delivered subject to the express condition that such risk is accepted by the Client and such other persons. Some conditions are subject to change over time and those making use of the Report should be aware of this possibility and understand that the Report only presents the conditions at the sampled points at the time of sampling. If special concerns exist, or the Client has special considerations or requirements, the Client should disclose them so that additional or special investigations may be undertaken which would not otherwise be within the scope of investigations made for the purposes of the Report.
- b) Reliance on Provided Information: The evaluation and conclusions contained in the Report have been prepared on the basis of conditions in evidence at the time of site inspections and on the basis of information provided to Thurber. Thurber has relied in good faith upon representations, information and instructions provided by the Client and others concerning the site. Accordingly, Thurber does not accept responsibility for any deficiency, misstatement or inaccuracy contained in the Report as a result of misstatements, omissions, misrepresentations, or fraudulent acts of the Client or other persons providing information relied on by Thurber. Thurber is entitled to rely on such representations, information and instructions and is not required to carry out investigations to determine the truth or accuracy of such representations, information and instructions.
- c) Design Services: The Report may form part of design and construction documents for information purposes even though it may have been issued prior to final design being completed. Thurber should be retained to review final design, project plans and related documents prior to construction to confirm that they are consistent with the intent of the Report. Any differences that may exist between the Report's recommendations and the final design detailed in the contract documents should be reported to Thurber immediately so that Thurber can address potential conflicts.
- d) Construction Services: During construction Thurber should be retained to provide field reviews. Field reviews consist of performing sufficient and timely observations of encountered conditions in order to confirm and document that the site conditions do not materially differ from those interpreted conditions considered in the preparation of the report. Adequate field reviews are necessary for Thurber to provide letters of assurance, in accordance with the requirements of many regulatory authorities.

6. RELEASE OF POLLUTANTS OR HAZARDOUS SUBSTANCES

Geotechnical engineering and environmental consulting projects often have the potential to encounter pollutants or hazardous substances and the potential to cause the escape, release or dispersal of those substances. Thurber shall have no liability to the Client under any circumstances, for the escape, release or dispersal of pollutants or hazardous substances, unless such pollutants or hazardous substances have been specifically and accurately identified to Thurber by the Client prior to the commencement of Thurber's professional services.

7. INDEPENDENT JUDGEMENTS OF CLIENT

The information, interpretations and conclusions in the Report are based on Thurber's interpretation of conditions revealed through limited investigation conducted within a defined scope of services. Thurber does not accept responsibility for independent conclusions, interpretations, interpolations and/or decisions of the Client, or others who may come into possession of the Report, or any part thereof, which may be based on information contained in the Report. This restriction of liability includes but is not limited to decisions made to develop, purchase or sell land.



**ALBERTA TRANSPORTATION AND ECONOMIC CORRIDORS GRMP (CON0022163)
NORTH CENTRAL (ATHABASCA AND FORT McMURRAY DISTRICTS)
INSTRUMENTATION MONITORING RESULTS**

SPRING 2025

**APPENDIX A
DATA PRESENTATION AND SITE PLANS**

SITE NC025: HWY 646:04 LINDBERGH HILL

**ALBERTA TRANSPORTATION AND ECONOMIC CORRIDORS
NORTH CENTRAL REGION - ATHABASCA AND FORT McMURRAY DISTRICTS
INSTRUMENTATION MONITORING FIELD SUMMARY (NC025)
SPRING 2025**

Location: Lindberg Hill (HWY 646:04 C1 16.082)	Readout: RST Vibrating wire readout 2106, unit 1/DGSI Dipmeter
File Number: 32122	Casing Diameter: 2.75"
Probe: RST SET 8R	Temp: 12
Cable: RST SET 8R	Read by: NKR/GE

SLOPE INCLINOMETER (SI) READINGS

SI#	GPS Location (UTM 12)		Date	Stickup m	Depth from top of casing (ft)	Azimuth of A+ Groove	Current Bottom Depth Readings				Probe/ Reel #	Size (")	Remarks
	Easting (m)	Northing (m)					A+	A-	B+	B-			
SI02-1	522385.00	5969334.00	22-May-25	0.82	49 to 3	16	-619	728	-721	-728	8R	2.75	
SI07-1*	522428.20	5969328.17	22-May-25	0.47	67 to 5	5	194	-175	-292	298	8R	2.75	***
SI07-2*	522428.20	5969328.17	22-May-25	0.66	61 to 5	5	-43	60	342	-337	8R	2.75	
SI07-3*	522428.20	5969328.17	22-May-25	0.76	49 to 3	355	496	-483	119	-117	8R	2.75	

STANDPIPE PIEZOMETER (SP) READINGS

SP#	GPS Location (UTM 12)		Date	Stick-up (m)	Reading below top of casing (m)	Bottom Pipe Depth (below top of casing (m)
	Easting (m)	Northing (m)				
SP02-1	522398.88	5969352.84	22-May-25	0.86	7.05	7.06
SP02-4	522393.12	5969402.21	22-May-25	0.77	2.60	9.14


LOAD CELL (VC) READINGS

Anchor#	VC#	GPS Location		Date	Reading B(units)	Temp degree C
		Latitude	Longitude			
G9U	VC1467	-	-		6335.4/6742.8/6855.0	8.6
G19U	VC1468	-	-		6511.1/6609.5/6254.9/6672.9	7.5
G19L	VC1466	-	-		6447.2/6070.6/6352.0/6676.2	7.1
G28U	VC1464	-	-		6411.9/6739.7/6479.0	10.5
G28L	VC1465	-	-		6792.9	**Not Working
G37	VC1463	-	-		6707.3/6717.0/6705.0	9.6

INSPECTOR REPORT

*SI07-1,2,3 were installed in the wall.
Use RST with 1 ft extension.
***SI07-1 hard to pull at 6 ft
Note: 4 SENSOR ON VW MONITOR SETTING
** Temp. sensor not working, only one Vibrating wire functioning

C:\Users\Michelle.Lapdata\localtemp\AcPublish_16216\32122-NC025.dwg-Jul. 29, 2021 2:25pm



LEGEND

- TEST PIT
- SLOPE INCLINOMETER (OPERATIONAL)
- STANDPIPE PIEZOMETER
- DAMAGED
- SLOPE INCLINOMETER (SHEARED OFF)
- LOAD CELL
- DIRECTION OF MOVEMENT IN SLOPE INCLINOMETER

0 10 20 30 40 50m
SCALE 1:750

BASE PLAN SURVEYED BY EXH ENGINEERING SCIENCES LTD.




NORTH CENTRAL
(ATHABASCA AND FORT MCMURRAY DISTRICTS)
NC025: HWY 646:04 (km 16)
WEST LINDBERGH HILL SLIDE
SITE PLAN SHOWING APPROXIMATE
INSTRUMENT LOCATIONS
DWG No. 32122-NC025

DRAWN BY	ML
DESIGNED BY	BWN
APPROVED BY	TSA
SCALE	1:750
DATE	JULY 2021
FILE No.	32122



Thurber Engineering Ltd.




HWY 646:04 Lindbergh Hill, Inclinometer SI02-1

Alberta Transportation

Sets marked * include zero shift and/or rotation corrections.

Thurber Engineering Ltd.




HWY 646:04 Lindbergh Hill, Inclinator SI02-1

Alberta Transportation

Sets marked * include zero shift and/or rotation corrections.


Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinometer SI07-1

Alberta Transportation


Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinometer SI07-1

Alberta Transportation


Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinometer SI07-1

Alberta Transportation


Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinator SI07-1

Alberta Transportation

Thurber Engineering Ltd.




HWY646:04 Lindbergh Hill, Inclinometer SI07-2

Alberta Transportation

Sets marked * include zero shift and/or rotation corrections.

Thurber Engineering Ltd.




HWY646:04 Lindbergh Hill, Inclinometer SI07-2

Alberta Transportation

Sets marked * include zero shift and/or rotation corrections.

Thurber Engineering Ltd.




HWY646:04 Lindbergh Hill, Inclinometer SI07-2

Alberta Transportation

Sets marked * include zero shift and/or rotation corrections.


Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinator SI07-2

Alberta Transportation


Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinometer SI07-3

Alberta Transportation


Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinometer SI07-3

Alberta Transportation


Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinometer SI07-3

Alberta Transportation

Thurber Engineering Ltd.



HWY646:04 Lindbergh Hill, Inclinator SI07-3

Alberta Transportation

FIGURE NC025-1
STANDPIPE PIEZOMETER DATA FOR HWY 646:04, LINDBERG HILL




FIGURE NC025-2
LOAD CELL DATA FOR HWY 646:04, LINDBERG HILL

