BF 07135 Local Road Over Bear River
Hydrotechnical Summary

Channel Capacity :

S = 0.0003
B = 12 m, h = 2.5 m, T_h = 22 m
Use AT equation

At Bank Height : Y = 2.5 m, V = 0.8 m/s, Q = 35 cms
At Channel Capacity : Y = 3.5 m, V = 1.1 m/s, Q = 75 cms

Historical Highwater Data :

A 1969 report refers to a HWM with Y = 2.4m. HW was observed at BF09050 just u/s in June 1990 (Y = 3.0m).

Gauge 07GE004 (DA = 1190 km^2, 1969 – Now) has recorded spot levels on Bear Lake just d/s with the highest levels in May 1974 and May 1997. There is no reference to a 1974 event on bridges on this stream, but there is a reference to the 1997 event at some of the bridges further upstream and at gauge 07GE007 (u/s of La Glace Lake, DA = 180 km^2, operating 1985 - 1999) where the highest recorded flow of 36cms was recorded on April 18, 1997. The June 1990 storm covered lower parts of the basin with 140mm and upper parts with about 100mm. A slight shift in location would have resulted in much higher input. Other large events are the June storms of 1964 and 1965.

Basin Runoff Potential :

d = 60mm, T_p = 20 hrs, q = 0.83 cms/km^2.
Gross DA = 1135 km^2.
Q_p = 940 cms.

Conclusion :

The channel capacity estimate exceeds historic observations and is within the basin runoff potential.

Recommended parameters : Y = 3.5 m, V = 1.1 m/s, Q = 75 cms.