BF 07419 Hwy 672 Over Bear River
Hydrotechnical Summary

Channel Capacity :

S = 0.0008
B = 8 m, h = 3.3 m, T_h = 15 m
Use n = 0.04

At Bank Height : Y = 3.3 m, V = 1.2 m/s, Q = 45 cms
At Channel Capacity : Y = 4.3 m, V = 1.5 m/s, Q = 80 cms

Historical Highwater Data :

HW was noted in spring 1963 with erosion of the east headslope of old bridge (during construction of new bridge). HW was also noted in June 1990 (Y = 3.9m), with V ~ 1m/s at 0.6m lower. Reports from 1960 and 1961 refer to HWM with Y = 3.3 – 4.5m. The 1996 BIM report notes a HWM with Y = 1.5m.

Gauge 07GE004 (DA = 1190 km^2, 1969 – Now) has recorded spot levels on Bear Lake just d/s with the highest levels in May 1974 and May 1997. There is no reference to a 1974 event on bridges on this stream, but there is a reference to the 1997 event at some of the bridges further upstream and at gauge 07GE007 (u/s of La Glace Lake, DA = 180 km^2, operating 1985 - 1999) where the highest recorded flow of 36cms was recorded on April 18, 1997. The June 1990 storm covered lower parts of the basin with 140mm and upper parts with about 100mm. A slight shift in location would have resulted in much higher input. Other large events are the June storms of 1964 and 1965.

Basin Runoff Potential :

d = 60mm, T_p = 20 hrs, q = 0.83 cms/km^2.
Gross DA = 700 km^2.
Q_p = 580 cms.

Conclusion :

The channel capacity estimate exceeds historic observations and is within the basin runoff potential.

Recommended parameters : Y = 4.3 m, V = 1.5 m/s, Q = 80 cms.