




- ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE
- AT DECK JOINT LOCATIONS, GIRDERS SHALL RECEIVE THE FOLLOWING COATING SYSTEM IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR BRIDGE CONSTRUCTION SECTION 6
 - A COMPLETE SF2, SF3 OR SF4 APPROVED BRIDGE COATING SYSTEM SHALL BE APPLIED TO THE BOTTOM FLANGE SURFACES (UNDERSIDE, TOP AND EDGES)
 - THE FAYING SURFACE OF UNDERSIDE OF GIRDER BOTTOM FLANGE IN APPROVED ORGANIC ZINC EPOXY PRIMER
- AT PIER BEARINGS AND SEMI-INTEGRAL ABUTMENT BEARINGS, AN APPROVED ORGANIC ZINC EPOXY PRIMER SHALL BE APPLIED TO THE UNDERSIDE OF GIRDER BOTTOM FLANGES IN CONTACT WITH THE BEARING



NOT FOR CONSTRUCTION

    					RECOMMENDED DIRECTOR BRIDGE ENGINEERING 	 STEEL PLATE GIRDER BRIDGE TYPICAL DETAILS SHEET 1			
									APPROVED EXECUTIVE DIRECTOR TECHNICAL STANDARDS BRANCH 
REV	DATE	REVISION		BY	 	DATE	SHEET	DRAWING	
DESIGNER	CM	CHECKER	MT	DATE		2020-04	1 OF 2	T-1759-20	